

CLAAS

AGRIGREASE LC

00/000

Multi purpose extreme pressure fluid lithium/calcium grease

APPLICATIONS

Centralized lubrication system grease

- Especially developed for chassis lubrication by means of a centralized system for which NLGI 00/000 grade greases are recommended.
- Central lubrication systems found on off-road vehicles used in agriculture and civil engineering.
- Always avoid contamination of the grease when applying. Preferably use a pneumatic pump system.

PERFORMANCES

Approved by manufacturers

- ISO 6743-9 : L-XECFB000
- DIN 51502 : MP00/000K-45
- The formulation is approved by the following OEMs :
MERCEDES BENZ, MAN
WILLY VOGEL
LINCOLN

CUSTOMER BENEFITS

Operability

Miscibility

No harmful substances

- Forms a durable lubrication film, resulting in prolonged lifetime of the lubricated parts.
- Thank to its excellent low temperature characteristics and smooth texture, has an outstanding pumpability.
- Miscible with most other conventional soap greases.
- Excellent adhesion to metal.
- Does not contain lead, or other heavy metals considered harmful to human health and the environment

CHARACTERISTICS

CLAAS AGRIGREASE LC 00/000	Units	
NLGI grade		00/000
Soap/thickener		Lithium/ Calcium
Color		Green
Appearance		Smooth
Operating temperature range	°C	-45 to 120
Dropping point	°C	> 170

The typical characteristics mentioned represent mean values.

CLAAS AGRIGREASE LC 00/000
May 2005
MPR N°0505

Developed with TOTAL
technology at the service of
CLAAS

This lubricant used in accordance with our recommendations and for the application for which it is intended does not represent a special hazard. A safety data file conforming to the requirements of current E.U. legislation is available from your local trade consultant.