

CLAAS AGRIMOT SDX

15W-40

Very high performance multigrade oil specifically intended for lubricating naturally aspirated and turbocharged diesel engines in new generation CLAAS / RENAULT agricultural tractors and equipments.

APPLICATIONS

**All CLAAS / RENAULT
Phase I, II, IIIa
Engines**

throughout the year

- Intended for lubricating CLAAS / RENAULT agricultural engines, particularly those of recent technology that satisfy the EUROPE Phase IIIa (2006) pollution control standard.
- Can be used in all tractor diesel engines including those not pollution controlled or which satisfy the Phases I (1999) or II (2003) standard.
- Particularly recommended for powerful engines or those used in severe conditions.
- Can be used in all agricultural Diesel or Gazoline engines, including those that are naturally aspirated.

PERFORMANCES

Classifications

ACEA : E7 / E5
API : CI-4 / SJ

Manufacturers approvals

MERCEDES-BENZ : MB-Approval 228.3
CUMMINS : CES 20078 (20077 / 20076)

Conforms to the specifications

CATERPILLAR : ECF-1a and ECF-2

Suitable for engines

DEERE, DEUTZ, IVECO...

CUSTOMER BENEFITS

Total safety

Longer oil change intervals

Simpler overall lubrication

- High thermal stability, ensuring excellent lubrication of hot parts of the engine even in summer.
- Excellent oxidation resistance, guaranteeing the life of the engine, particularly in case of longer oil-change intervals.
- Good fluidity when cold, for easier starting.
- Can be used for lubricating all types of engine, including older models (not pollution controlled).

CHARACTERISTICS

| AGRIMOT SDX | Units | 15W-40 |
|------------------------------|--------------------|--------|
| Kinematic viscosity at 40°C | mm ² /s | 114 |
| Kinematic viscosity at 100°C | mm ² /s | 14.5 |
| Viscosity index | | 130 |
| Pour point | °C | -30 |

The typical characteristics mentioned represent mean values.

AGRIMOT SDX 15W-40
Sheet updated : 07/2009
Sticker reference : FT 05.05

Developed with TOTAL
technology at the service of
CLAAS